

DS-K3B601 Swing Barrier



The DS-K3B601 series swing barrier with 12 pairs of IR lights is designed to detect unauthorized entrance or exit. By adopting the swing barrier integratedly with the access control system, person should authenticate to pass through the lane via swiping IC or ID card, scanning QR code, etc. It is widely used in attractions, stadiums, construction sites, residences, etc.

- 12 pairs of IR light detectors: Permissions validation and anti-tailgating
- LED light indicates passing direction
- Audible and visual nipping alarm: The barrier will stop working for a period of time when detecting obstruction when open/close barrier
- Self-detection, Self-diagnostics, and automatic alarm
- Valid passing duration settings: System will cancel the passing permission if a person does not pass through the lane within the valid passing duration
- Door remaining open when fire alarm triggered: The barrier will open automatically when alarm is triggered
- Barrier is in free status when powering down



▪ Specification

System	
MCBF	> 6 million times
Motor	Servo motor
Interface	
Network interface	1
RS-485	4
RS-232	4
Lock output	2
IO input	4
IO output	4
Capacity	
Card capacity	60,000
Event capacity	180,000
General	
Throughput	30 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method.
Power supply method	100 to 240 VAC; 50 to 60 Hz
IR light detectors	12 pairs
Working temperature	-25 °C to 70 °C (-13 °F to 158 °F)
Lane width	550 mm to 1100 mm (21.65" to 43.31")
Working humidity	10% to 95% (No Condensing)
Barrier material	Stainless steel pipe; Acrylic glass
Pedestal material	SUS304 stainless steel
Dimensions	Without Packaging: 1500 mm × 200 mm × 990 mm (59.06" × 7.87" × 38.98") With Packaging: 1610 mm × 300 mm × 1100 mm (63.39" × 11.81" × 43.31")
Weight	Without packaging: 72 kg (left and right)/85 kg (middle) (158 lb/187 lb) With packaging: 102 kg (left and right)/115 kg (middle) (225 lb/253 lb)
Approval	CE/FCC/CB/RoHS/REACH/WEEE

▪ Maintenance

The main element of the turnstile is stainless steel, which is rustless (antioxidant) and corrosion resistant (The anti corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically .

The instructions and tips for maintaining the turnstile are as follows:


- Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seashores and chemical plants.
- Keep the device surface clean and dry.
- Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.
- Use sourcing pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.

- Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggest to clean the
- device every month in common circumstances and every week for severe environments (seaside and chemical plants for
- instance).

▪ Available Model

DS-K3B601-L, DS-K3B601-M, DS-K3B601-R

▪ Dimension



▪ **Accessory**

▪ **Optional**

DS-KAB-601COVE				
DS-K5671-ZV Face Recognition Module For Turnstile	R Barrier's Face Recognition Install Hole's Cover	DS-K3B601-BASE Swing Barrier Base Module	DS-K5671-ZU Face Recognition Module For Turnstile	DS-K5671-ZH Face Recognition Module For Turnstile
				
DS-K3B601-BASE Swing Barrier Base Module				
				

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com