

DS-K3B801SX Swing Barrier



The swing barrier with two barriers and 24 pairs of IR lights is designed to detect unauthorized entrance or exit. By adopting the swing barrier integrated with the access control system, person should authenticate to pass through the lane via swiping IC or ID card, scanning QR code, etc. It is widely used in attractions, stadiums, construction sites, residences, etc.

- TCP/IP network communication: The communication data is specially encrypted to relieve the concern of privacy leak
- Permissions validation and anti-tailgating
- Bidirectional (Entering/Exiting) lane: The barrier opening and closing speed can be configured according to the visitors flow
- The barrier will be locked or stop working when people are nipped
- Self-detection, Self-diagnostics, and automatic alarm
- Audible and visual alarm will be triggered when detecting intrusion, tailgating, reverse passing, climbing over barrier, and overstay
- Fire alarm passing: When the fire alarm is triggered, the barrier will be open automatically for emergency evacuation.



▪ Specification

Model		DS-K3B801SX
System	MCBF	> 6 million times
	Motor	Servo motor
Interface	Network interface	1
	RS-485	4
	RS-232	4
	Lock output	2
	IO input	4
	IO output	4
Capacity	Card capacity	60,000
	Event capacity	180,000
General	Throughput	30 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method
	Power supply method	100 to 240 VAC; 50 to 60 Hz
	IR light detectors	24 pairs
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Lane width	550 mm to 1100 mm (21.65" to 43.31")
	Working humidity	10% to 95% (No Condensing)
	Barrier material	Acrylic glass
	Pedestal material	SUS304 stainless steel with the thickness of 2 mm (0.08")
	Dimensions	With packaging: 1688 mm × 348 mm × 1318 mm (66.5" × 13.7" × 51.9") Without packaging: 1500 mm × 160 mm × 1010 mm (59.1" × 6.3" × 39.8")
	Application environment	Indoor
	Weight	Left and right pedestal: 146.5 kg (323.0 lbs) Middle pedestal: 170.4 kg (375.7 lbs)
Approval	CE/FCC/CB/RoHS/REACH/WEEE	

▪ Maintenance

The main element of the turnstile is stainless steel, which is rustless (antioxidant) and corrosion resistant (The anti corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically .


The instructions and tips for maintaining the turnstile are as follows:

- Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seashores and chemical plants.
- Keep the device surface clean and dry.
- Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.
- Use scouring pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.
- Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggested to clean the device every month in common circumstances and every week for severe environments (seaside and chemical plants for instance).

▪ **Available Model**

DS-K3B801SX-L, DS-K3B801SX-M, DS-K3B801SX-R

▪ **Dimension**



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com