

DS-2CE56C0T-IT1F 1 MP Fixed Turret Camera



- HD 720p turret camera
- EXIR 2.0: advanced infrared technology with 20 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

| Camera | |
|------------------------|---|
| Image Sensor | 1 MP CMOS |
| Max. Resolution | 1280 (H) × 720 (V) |
| Min. Illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s |
| Day & Night | IR Cut Filter |
| Angle Adjustment | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | Fixed focal lens, 3.6, 2.8, 6, and 8 mm optional |
| Focal Length & FOV | 70.9°(3.6 mm), 92°(2.8 mm), 56.7°(6 mm), 38.6°(8 mm) |
| Lens Mount | M12 |
| Illuminator | |
| Supplement Light Range | Up to 20 m, supplement light type = IR |
| Image | |
| Frame Rate | 720p@25fps/720p@30fps |
| SNR | > 62dB |
| Interface | |
| Video Output | 1 HD analog output |
| General | |
| Power | 12 VDC ± 15%, max. 4 W |
| Dimension | Φ 110 mm × 93.2 mm (4.33" × 3.67") |
| Weight | Approx. 350 g (0.77 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing) |
| Approval | |
| Protection | IP67 |

▪ Available Model





DS-2CE56C0T-IT1F(2.8mm)

DS-2CE56C0T-IT1F(3.6mm)

DS-2CE56C0T-IT1F(6mm)

▪ Accessory

▪ Optional

| DS-1275ZJ-SUS Vertical Pole Mount | DS-1281ZJ-S Inclined Ceiling Mount | DS-1276ZJ-SUS Corner Mount | DS-1280ZJ-S Junction Box | DS-1272ZJ-110-TRS Wall Mount |
|---|---|---|---|---|
|  |  |  |  |  |
| DS-1280ZJ-TR13 | | | | |
|  | | | | |

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

