

DS-2CE56C0T-IT3F 1 MP Fixed Turret Camera



- HD 720p turret camera
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Camera	
Image Sensor	1 MP CMOS
Signal System	PAL/NTSC
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Max. Resolution	1280 (H) × 720 (V)
Lens	
Lens Type	Fixed focal lens, 2.8 mm, 3.6mm, 6 mm, 8 mm, 12 mm, and 16 mm optional
Focal Length & FOV	Field of view : 70.9° (3.6 mm), 92° (2.8 mm), 56.7° (6 mm), 38.6° (8 mm), 27.5°(12 mm), 17.7° (16 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 40 m
Image	
Frame Rate	720p@25fps/720p@30fps
SNR	>62 dB
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC±15%, max. 4 W
Dimension	Φ110 mm × 93.2 mm (Φ 4.33" × 3.67")
Weight	Approx. 350 g (0.77 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Approval	
Protection	IP67

▪ Available Model

DS-2CE56C0T-IT3F(2.8mm)

DS-2CE56C0T-IT3F(3.6mm)







DS-2CE56C0T-IT3F(6mm)

DS-2CE56C0T-IT3F(8mm)

DS-2CE56C0T-IT3F(12mm)

▪ **Accessory**

▪ **Optional**

DS-1272ZJ-110-TRS Wall Mount	DS-1281ZJ-S Inclined Ceiling Mount	DS-1276ZJ-SUS Corner Mount	DS-1280ZJ-S Junction Box	DS-1280ZJ-TR13
				
DS-1275ZJ-SUS Vertical Pole Mount 				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

