

DS-2CE5AU1T-VPIT3ZF 4K Vandal Motorized Varifocal Dome Camera



- 8 MP dome camera
- Lens focuses automatically when zooming in or out
- EXIR 2.0: advanced infrared technology with 60 m IR distance
- Water and dust resistant (IP67) and vandal proof (IK10)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification









Camera	
Image Sensor	8.29 megapixel progressive scan CMOS
Max. Resolution	3840 (H) × 2160 (V)
Min. Illumination	Color: 0.01 Lux @ (F2.4, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/12.5s to 1/50, 000 s,NTSC: 1/15 s to 1/50, 000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°, Rotate: 0° to 355°
Signal System	PAL/NTSC
Lens	
Lens Type	2.7 mm to 13.5 mm motorized vari-focal lens
Focal Length & FOV	108.1° to 45.6°
Lens Mount	Φ14
Image	
Image Settings	Brightness, Sharpness, DNR, Mirror, Smart IR, HLC
Frame Rate	TVI: 8MP@12.5fps, 8MP@15fps, 5MP@20fps, 4MP@25fps, 4MP@30fps, 2MP@25fps,,2MP@30fps,CVI: 8MP@12.5fps, 8MP@15fps,AHD: 8M@12.5fps, 8M@15fps,CVBS: 960H P/N
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	DWDR
Image Enhancement	BLC
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Material	Metal
Dimension	Ø 145 mm × 111.3 mm (Ø 5.69" × 4.37")
Weight	Approx. 860 g (1.90lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Power Supply	9 VDC to 15 VDC,-A: 9.6 VDC to 14.4 VDC; 19.2 VAC to 28.8 VAC,*You are recommended to use one power adapter to supply the power for one camera.
Consumption	Max. 6.4 W,-A: Max. 8.2 W
IR Range	Up to 60 m
Approval	
Protection	IP67

▪ Available Model

DS-2CE5AU1T-VPIT3ZF(2.7-13.5mm)

▪ **Accessory**

▪ **Optional**

DS-1275ZJ-SUS(Grey)#UK	DS-1253ZJ-L Rain Shade	DS-1281ZJ-DM45	DS-1280ZJ-DM45 Junction Box	DS-1276ZJ-SUS Corner Mount
				
DS-1275ZJ-SUS Vertical Pole Mount	DS-1271ZJ-140-DM 45	DS-1273ZJ-140-DM 45		
				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

