

iDS-TP60-12L Smart Traffic Data Analysis Server



Features and Functions

Smart Functions

- GPU architecture with deep-learning algorithm. Real-time analysis of 1 million pictures every day.
- Vehicle type and color recognition.
- License plate recognition and no helmet detection for motorbike.

Professionalism and Reliability

- Pluggable HDD for convenient installation and maintenance.
- Professional embedded hardware and software to guarantee the reliability of system operation.
- Data network interfaces and management network interfaces to raise the system safety.
- Low power consumption and low heat dissipation.

HD Input

- Up to 12 IP cameras connection.
- Live view, record, and playback of 3 MP, 7MP, and 9 MP cameras.

HD Output

- Live view via HDMI output.
- Live view via web browser.

HD Storage

- 1 1 T HDD for record and picture storage.
- ANR.

HD Transmission

- 2 self-adaptive 100/1000M network interfaces, 4 self-adaptive 10/100M network interfaces, and 1 optical interface.

Various Applications


- Centralized management of connected IP cameras, including system configuration, information import and export, real-time information display, data management and search, data export, upgrade, etc.
- Connectable to Hikvision smart IP cameras to realize live view, playback, and event alarm.
- Time synchronization by GPS, NTP, SDK, etc.
- Provides power supply to external devices (e.g., external HDD) with 12 VDC.
- One-key restoration to factory settings.
- Supports listening mode and uploading data to Hikvision iVMS-8600.
- Provides SDK for secondary development by third-party manufacturer.



Specifications

Model	iDS-TP60-12L
Operating Interface	WEB, HDMI
HDD Storage	1 2.5" 1 T HDD
Network Interface	1 optical interface 4 10/100M self-adaptive Ethernet interfaces, 2 100/1000M self-adaptive Ethernet interfaces
Analog Video Input	4-ch HDTVI video inputs
IP Video Input	Up to 12-ch 7 MP IP cameras connection
Audio Input	1-ch
Audio Output	1-ch
Alarm Input	2-ch
Alarm Output	2-ch
USB Interface	2 × USB 2.0
RS-232 Interface	2
RS-485 Interface	2
Indicator	UID indicator, Alarm indicator, Power indicator, Ready indicator
Memory	2 × 2 GB
TX1 Chip	2
Button	Power on/off, Reset
Power Supply	12 VDC/5A
Dimensions (W × D × H)	300 × 227.5 × 74.1 mm (11.8 × 9.0 × 2.9 inch)
Operating Temperature	-20 °C to +55 °C (-4 °F to +131 °F)
Operating Humidity	10% to 90%
Weight	3.6 kg (7.9 lb)

Panel Interfaces



No.	Name	No.	Name
1	RS-232 serial interface	9	RS-485 serial interface
2	Power switch		RS-232 serial interface
3	GND		Alarm input
4	10/100M self-adaptive Ethernet interfaces		Alarm output
5	100/1000M self-adaptive G2/G1 Ethernet interface	10	USB 2.0 interfaces
6	Optical interface	11	12 VDC power input
7	Video inputs	12	Status indicators
8	HDMI interface		

Available Models

iDS-TP60-12L

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com