

## DS-2TS16-50VI/W

Handheld Thermal & Optical Bi-spectrum Binocular



Hikvision DS-2TS16-50VI/W Handheld Thermal & Optical Bi-spectrum Binocular is equipped with ultra-low light optical detector, 640 × 512 thermal detector, 1024×768 OLED display and eyepiece with large field of view. The device can quickly discover and locate hiding objects even under extreme environment, such as smoke, fog, rain and snow. It can be widely applied to scenarios like patrol, law enforcement, search and rescue, drug enforcement, anti-smuggling and suspect capture.

### Key Features

- Thermal: 640 × 512@25fps, optical: 1280 × 960@25fps
- NETD < 40mk (@25 °C,F#=1.0)
- DDE (Digital Detail Enhancement)
- 3D DNR, adaptive AGC (Automatic Gain Control)
- Ultra-low illumination (optical channel), B/W: 0.001 lux @ (F1.0 , AGC On )
- 0.39-inch OLED display
- Automatic OLED backlight
- Manual focus for thermal lens
- Bi-spectrum image fusion and object highlight (detail enhancement and target recognition)
- Video recording, replay, picture snapshot and search (capable to review the event on device)
- Wi-Fi hot spot, GPS, cursor display
- Up to 7 hours continuous running
- IP67



## Specifications

Model	DS-2TS16-50VI/W
Parameter	Handheld Observational Thermal & Optical Bi-spectrum Binocular
<b>Thermal Module</b>	
Image sensor	Uncooled Focal Plane Arrays
Max. Resolution	640 × 512@25fps
Pixel Pitch	17μm
Response waveband	8μm to 14μm
NETD	< 40mk (@25 °C,F#=1.0)
Lens (focal length)	50mm, Manual focus
MRAD (IFOV)	0.34
Field of View	12.42 ° × 9.95 °
Aperture	F 1.0
Digital Zoom	4×
<b>Optical Module</b>	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	B/W : 0.001 lux @ (F1.0 , AGC On )
Max. Resolution	1280 × 960@25fps
Lens (focal length)	12mm
Image Enhancement	3D DNR, Adaptive AGC
<b>Image Display</b>	
Monitor	0.39-inch, OLED, 1024 × 768
Thermal/Optical Mode	Thermal view, B/W optical view, image fusion view are selectable
Image Fusion	Color fusion, B/W fusion
Palettes	Black hot, white hot
<b>Smart</b>	
Hot Track	Yes
Object Highlight	Yes
Cursor Display	A cursor shows in the view for roughly measuring distance from the target.
Automatic Backlight	The OLED backlight automatically turns off if no human eyes are detected.
<b>System</b>	
Storage	Built-in memory module (32GB)
Record Video	On-board video recording
Snapshot	On-board image capturing
Video Replay	Yes
Picture Search	Yes
Wi-Fi	Yes
GPS	Yes
<b>Power Supply</b>	
Battery Type	Four 18650 batteries, requires 5 hours to be fully charged
Battery Operating Time	≥7h
Battery Capacity Display	Yes
<b>General</b>	
Power	5V DC/2A

Working Temperature	-30 °C to 55 °C (-22 °F to 131 °F)
Protection level	IP67
Mounting	UNC 1/4"-20
Cable Output	Aviation plug: connecting to BNC, DB9, and USB
Accessories (Supplied)	Battery charger, battery charger power cable, wiping cloth, two wrist straps, User manual, aviation plug cable, eight batteries
Dimension (L x W x H)	164mm × 182.3mm × 73.3mm (6.46" × 7.18" × 2.89")
Weight	<1.0kg (2.20 lb)

## Wide Range Coverage for Different Specifications


**Note:** The table below is only for reference, the performance varies from model to model, and the specific data is based on 17 μm pixel pitch.

Lens (focal length)	50mm
Detection range (Vehicles)	4510m
Detection range (Humans)	1471m
Recognition range (Vehicles)	1127m
Recognition range (Humans)	368m
Identification range (Vehicles)	564m
Identification range (Humans)	184m

## Order Models

DS-2TS16-50VI/W

## Dimensions



Distributed by



## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com

0200001080831