

DS-PEAP-CVS1 Video Panic Alarm Panel



- Adopts embedded Linux operation system and high-performance embedded SOC processor
- Supports network adaptive and video and audio adaptive to realize low latency
- H.264, H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, HIK-SIP, RTSP, ONVIF, and standard SIP
- Video collection and all-day monitoring with 2 MP HD camera
- Two-way audio function with up to 5 m communication distance
- build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface
- Protection level: IP65
- Explosion-proof level: IK10
- Braille on the buttons
- Support 3G/4G: FDD LTE(B1/B3/B5/B7/B8/B20), TDD LTE(B38/B40/B41), WCDMA(B1/B5/B8), GSM(B3/B8)

▪ Specification

| Software features | |
|----------------------------------|--|
| Wired network | 10 M/100 M Self-adaptive Ethernet port |
| Network encryption | Supports User Lock-in and Password Security Prompt |
| Cellular network | 3/4 G Communication |
| Hardware features | |
| SD card | Standard Micro SD Card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 256G |
| Tamper-Proof | Support |
| Video | |
| Fill light | Infrared Light |
| Resolution | 1920*1080 |
| Field angle | Horizontal: 109° Vertical: 86° Diagonal: 142° |
| Day/night switch mode | Auto switching |
| Video compression standard | H.264, H.265 |
| Frame rate | 25 fps |
| Audio | |
| Audio output | 1-ch 3 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output |
| Audio input | 1-ch Built-in Omnidirectional Microphone Pickup Distance: 2 m listening Distance: 10 m |
| Audio encoding/decoding standard | AAC, G.711, G.726, OPUS |
| Audio compression code rate | 16 Kbps, 64 Kbps |
| Audio quality | Smart Noise Suppression |
| Electrical characteristics | |
| Power supply | 12 VDC or RJ45 PoE |
| Operation humidity | 10%-90% |
| Operation temperature | -40 °C to 65 °C |
| Power consumption | ≤40 W |
| General | |
| IK rate | IK10 |
| IP rate | IP65 |
| Installation method | Wall-mounted |
| Dimension (W x H x D) | 190 x 119 x 47 mm |
| Application scenario | Outdoor |
| Shell material | Metal |
| Device management | |
| Alarm output | 2 |
| Alarm input | 2 |
| Camera | Built-in 2MP HD IR Camera IR Distance ≥ 10 m |

Report method

| | |
|----------|------------------------------|
| Protocol | TCP/IP, RTSP, HIK-SIP, ONVIF |
|----------|------------------------------|

▪ Available Model

DS-PEAP-CVS1

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq