

# DS-PEAP-CVSA1E Panic Alarm Station

DS-PEAP series panic alarm station is designed with 2MP HD camera, and dual network ports. It supports two-way audio. It helps to realize alarm aid the first time and provides more efficient service for building social stability. It is mainly applied to classroom, corridor, laboratory, dormitory, office, hospital, ward and so on.



#### Key Features

- Adopts embedded Linux operation system and high-performance embedded SOC processor
- Supports network adaptive and video and audio adaptive to realize low latency
- H.264, H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, HIK-SIP, RTSP, ONVIF, and standard SIP
- Video collection and all-day monitoring with 2 MP HD camera
- Two-way audio function with up to 5 m communication distance
- build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface
- Protection level: IP65
- Explosion-proof level: IK10
- Braille on the buttons





## Specification

Software features			
Wired network	10 M/100 M Self-adaptive Ethernet port		
Network encryption	Supports User Lock-in and Password Security Prompt		
Cellular network	3/4G Communication(AU)		
Hardware features			
Tamper-Proof	Support		
SD card	Standard Micro SD Card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 256G		
Video	, , , ,		
Video compression standard	H.264,H.265		
Frame rate	25fps		
	Horizontal: 109°		
Field angle	Vertical: 86°		
	Diagonal: 142°		
Day/night switch mode	Auto switching		
Electrical characteristics			
Operation temperature	-40°C to 65°C		
Power supply	12 VDC or RJ45 PoE		
Power consumption	≤40W		
Operation humidity	10% to 90%		
General			
Shell material	Metal		
Dimension(WxHxD)	229x138x44.5mm		
IP rate	IP65		
IK rate	IK10		
Application scenario	Outdoor		
Installation method	Embedded-mounted		
Audio			
	1-ch Built-in Omnidirectional Microphone		
Audio input	Pickup Distance: 2 m		
	listening Distance: 10 m		
	1-ch 3 W Build-in Loudspeaker		
Audio output	1-ch 3.5 mm Audio Interface for External Audio Output		
Audio encoding/decoding standard	AAC,G.711,G.726,OPUS		
Audio quality	Smart Noise Suppression		
Audio compression code rate	16Kbps,64Kbps		
Device management			
Alarm input	2		
Camera	Built-in 2MP HD IR Camera		
	IR Distance ≥ 10m		
Alarm output	2		
Report method			
Protocol	TCP/IP, RTSP, HIK-SIP, ONVIF		



#### Available Model DS-PEAP-CVSA1E

Distributed by		
_		

### **HIKVISION**°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com