

DS-PEA3M-21



- One-touch emergency calling
- High quality imaging with 2 MP bulit-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 128
 GB
- Supports siren and audio expansion
- Integrates with speed dome cameras



Specification

Software features	
Wired network	10 M/100 M Self-adaptive Ethernet port
Hardware features	
Tamper-Proof	tamper alarm
Electrical locker	Electronic Controlled Cabinet Lock/Normal Cabinet Lock
Netowrk interface	1RJ45,10 M/100 M/1000 M self adaptive
Audio interface	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
	1-ch 3.5 mm Audio Interface for External Audio Input
PSTN	1
Bus	RS-485 1, Half-duplex
SD card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
Loudspeaker	110dB, Sound Can be Configured Separately
Video	
Frame rate	25fps
Resolusion	1920*1080
Field angle	Horizontal: 128°
	Vertical: 75°
	Diagonal: 147°
Day/night switch mode	IR Cut Filter
Audio	
Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
	1-ch 3.5 mm Audio Interface for External Audio Input
Intercom	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m
Audio output	1-ch 30 W Build-in Loudspeaker
	1-ch 3.5 mm Audio Interface for External Audio Output
Audio compression code rate	16Kbps,64Kbps
Electrical characteristics	
Power supply	110-240V AC
Operation temperature	-40 °C to +60 °C (-40 °F to 140 °F)
Operation humidity	10% to 90%
Power consumption	≤ 70 W
General	
General .	Without Bracket: 450 mm × 500 mm × 2205 mm (17.72" × 19.69" × 86.81")
Dimension(WxHxD)	With Bracket: 450 mm × 500 mm × 4500 mm (17.72" × 19.69" × 177.17")
Installation method	Ground Mounting
Device management	Ground mountains
Alarm input	2
Alarm output	2
Camera	2 MP HD IR Camera
Sounder output	110dB, Sound Can be Configured Separately
•	1 Red and Blue Alarm Lamp, Light Can be Configured Separately
Lamp Report method	1 Neu and blue Alaim Lamp, Light Can be Configured Separately
Report method	TCD/ID DTCD LIIV CID ONIVIE
Protocol	TCP/IP, RTSP, HIK-SIP,ONVIF



Available Model

DS-PEA3M-21





Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision_Global





