HIKVISION

DS-PDP15P-EG2-WB(B)
Wireless PIR Detector
Quick Start Guide

ENGLISH

1 APPEARANCE

1. Indicator
2. Bracket Tamper Port
3. Battery
4. Tamper Switch
5. Power Switch

2 ENROLLMENT

3 INSTALLATION

I. Check signal strength.
II. Install the device.
  a. Mount the detector with screw.
  b. Mount the detector with sponge tape.
III. (Optional) Install the device with bracket.

4 TEST

User Manual

Scan the QR code for more information and operation help.

Specification

Detection range	15 m (12 metre EN compliant), 90°
Auto sensitivity	Yes
Pet immunity	Up to 30 Kg (Height < 40 cm)
Tamper protection	Front & Back
LED indicator	Blue (alarm)
Operating temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operating humidity	10% to 90%
Installation height	1.8 to 2.4 m (nominal height = 2.1 m)
Dimension (W × H × D)	65.5 mm × 103 mm × 48.5 mm
Weight	128 g
Transmission frequency	433 MHz
RF range	1.2 Km (open area)
Battery	CR123A x 1 (included), 3 V/1600 mAh
Standard battery life	5 years
Low voltage value	2.45 V
Voltage range	Fully charged (new) to 2.45 VDC (battery)

Note: when the low voltage message appears there will be at least 30 days of use.

UD33817B

1



2



3



4



Detection Range: FOV 90°, 84 zones, 7 levels
Mounting Height: 1.8 to 2.4 m (typical 2.1 m)
Pet Immunity: 30 Kg



User Manual

ENGLISH

INSTALLATION CAUTION
The additional force shall be equal to three times the weight of the equipment but not less than 50N. The equipment and its associated mounting means shall remain secure during the installation. After the installation, the equipment, including any associated mounting plate, shall not be damaged.

ESPAÑOL

PRECAUCIONES DE INSTALACIÓN
La fuerza adicional debe ser equivalente a tres veces el peso del equipo, pero no inferior a 50 N. El equipo y el soporte asociado deben permanecer seguros durante la instalación. Tras la instalación, no se debe dañar el equipo ni tampoco las placas de montaje asociadas.

PORTUGUÊS (BRASIL)

CUIDADOS NA INSTALAÇÃO
A força adicional deve ser igual a três vezes o peso do equipamento, mas não inferior a 50 N. O equipamento e seus recursos de montagem associados devem permanecer seguros durante a instalação. Após a instalação, o equipamento, incluindo qualquer placa de montagem associada, não pode estar danificado.

SLOVENŠČINA

POZOR! NAMESTITEV
Dodatna sila mora biti enaka trikratni teži opreme, vendar ne manjša od 50 N. Poskrbite, da med namestitvijo ne poškodujete opreme in priloženih vgradnih pripomočkov. Po končani namestitvi pazite, da ne poškodujete opreme in morebitne vgradne plošče.

SRPSKI

UPOZORENJA O INSTALACIJI
Dodatna sila treba da bude jednaka trostrukoj težini opreme, ali ne manja od 50 N. Oprema i odgovarajući pribor za postavljanje treba da budu pričvršćeni tokom postavljanja. Posle postavljanja, oprema i ploča za postavljanje koju ste možda koristili ne smeju da budu oštećene.

HEBREW

אזהרות התקנה
הכח הנוסף חייב להיות שווה לפי שלושה ממשקל הציוד ולא פחות מ- 50N. הציוד והאביזרים הנלווים יותקנו בצורה מאובטחת במהלך ההתקנה. לאחר ההתקנה, אין לגרום נזק לציוד, כולל למשטח ההרכבה.

မြန်မာ

တပ်ဆင်ရေးခွင့်: သေတ္တာပြန်

အပို့ဆောင်ရေးအားသည် ကိရိယာအလေးချိန်၏ သုံးဆမှ နည်းရမည် မဟုတ်သော်လည်း 50N ထက် မနည်းသော် ကျော်ဝိရိယအားဖြင့် ပြောင်းလဲမှုကြောင့် ဒီဗာဒကုဗောဇည်းတင်ခြင်းကို တပ်ဆင်နိုင်ကြပြီး ဒီဗာဒကုဗောဇည်းတင်ခြင်းအပြီး ကိရိယာနှင့် သက်ဆိုင်သူ ဒီဗာဒကုဗောဇည်းများ အပြာကဲကဲ ပါဝင်သော်မျှ ပျက်စီးခြင်း ကင်းရှင်းရမည်။