

# DS-PDQP15AM-LM-WB Wireless 180° Panoramic Detector

Wireless 180° Panoramic Detector is a two-way wireless outdoor quad PIR detector with 180° lens coverage. This device is designed to protect the outdoor areas of your property and especially suitable for large free space applications.

- 180° panoramic coverage
- Active IR anti-masking
- IP65 weather resistance for outdoor application
- Multiple enrollment methods and easy installation
- Frequency hopping against jamming for reliable transmission



# Specification

Detection Performance			
Detection Method	Passive Infrared		
Sensor Model	SFG323-711		
Detection Range	15 m		
Detection Angle	180°		
Detection Zones	40		
Detectable Speed	0.3 to 2m/s		
Sensitivity	Auto, low		
White Light Filter	20000lux		
Pet Immunity			
·	Up to 40 kg(cm height)		
Digital Temperature Compensation	Support		
Anti-masking	Support		
Adaptable Coverage	Pattern mask included		
Feature			
Digital Processing	Support		
Sealed Optics	Support		
Tamper Protection	Front, rear		
Environment Temperature Indicator	Support		
Signal Strength Indicator	Support		
Interface			
Power Switch	Power up enrolling		
LED Indicator	Blue(alarm), green+orange(mask)		
Transmission			
Transmission Technology	Tri-X wireless		
Transmission Method	Two-Way RF wireless		
Transmission Frequency	433 MHz		
Transmission Security	AES-128 encryption		
Transmission Range(Free Space)	1.2 km		
Frequency Hopping	Support		
Enrolling Method	Power up, remote ID, QR code		
<b>Electrical Characteristics</b>			
Standard Battery Life	Up to 5 years (standby time) (The battery working time can be significantly reduced at low temperatures)		
Power Supply	Battery powered		
Battery Type	CR123A × 5		
Typical Voltage	3V		
General			
Operation Temperature	-25°C to 60°C (-13°F to 140°F)		
Storage Temperature	-25°C to 60°C (-13°F to 140°F)		
Operation Humidity	10% to 90%		
IP Rate	IP65		
Dimension(WxHxD)	75 mm × 202 mm × 73 mm		



Weight	512.5 g
Mounting Height	0.8 m to 1.2 m
Mounting Method	Wall
Application Scenario	Outdoor

#### Available Model

DS-PDQP15AM-LM-WB

### Accessory

## Optional

DS-PDP-EX-BATT	DS-PDP-IN-CR123A Indoor Detector Battery	DS-PDCM15PF-IR
	+ CR123A 3.0V -	



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision\_Global





