

THC-B123-M 2 MP Ultra Low Light Fixed Mini Bullet Camera



- 1080p bullet camera
- Good night-time performance with ultra-low light 0.005 lux
- Clear imaging against strong back light due to 120 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- EXIR 2.0: advanced infrared technology with 30 m IR distance.

▪ Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	Color: 0.005 Lux@(F2.0, AGC ON), B/W: 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm
Focal Length & FOV	Horizontal FOV 106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)
Lens Mount	M12
Illuminator	
Supplement Light Range	IR Distance: Up to 30 m
Smart Supplement Light	Yes
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness,Mirror,Sharpness,AGC
Frame Rate	PAL: 1080p@25fps, NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	≥120 dB
Image Enhancement	BLC,HLC
Noise Reduction	3D DNR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS,1 HD analog output
General	
Power	12 VDC ±25%, Max. 4.6 W *You are recommended to use one power adapter to supply the power for one camera.
Material	Metal
Dimension	165 mm × 62 mm × 58 mm (6.50" × 2.44" × 2.28")
Weight	Approx. 287 g (0.63 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing)
Language	English
Approval	
Protection	IP66

▪ Available Model

THC-B123-M(2.8mm)

THC-B123-M(3.6mm)

THC-B123-M(6mm)

▪ **Accessory**

▪ **Optional**

**HIA-J101
Junction Box**



HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

