

THC-T320-VF 2 MP Manual Varifocal Turret Camera



- 1080p vari-focal turret camera
- EXIR 2.0, advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP66)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification






Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	Color: 0.01 Lux@(F1.6, AGC ON), B/W: 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm to 12 mm
Focal Length & FOV	Horizontal FOV 111.5° to 33.4°
Lens Mount	Φ14
Illuminator	
Supplement Light Range	IR Distance: Up to 40 m
Smart Supplement Light	Yes
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080p@25fps, NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC
Noise Reduction	2D DNR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS, 1 HD analog output
General	
Power	12 VDC ± 15%, Max. 5 W
Material	Main body: Metal, Enclosure: Plastic
Dimension	Φ 120 mm × 105.06 mm (Φ 4.72" × 4.16")
Weight	Approx. 450 g (0.99 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing)
Language	English
Approval	
Protection	IP66

▪ Available Model

THC-T320-VF(2.8-12mm)

- **Accessory**

- **Optional**

HIA-J103 Junction Box	HIA-B101-130T Pendant Mount	HIA-B201 Corner Mount	HIA-B402-130T Wall Mount	HIA-J202 Inclined Ceiling Junction Box
				

HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

