Hilook

DVR-E04G-B 4-ch 1080p Lite 1U H.265 eSSD DVR

Key Feature

- Powered by eSSD technology
- Deep learning based human and vehicle targets classification of Motion Detection 2.0
- Scene-adaptive bitrate control video compression
- Up to 1080p Lite@30 fps encoding capability
- Low power consumption
- Audio via coaxial cable



Built-In SSD

- Minimalist eSSD design brings low power consumption
- Integrated storage design provides the plug-and-play device use

Easy Installation

- Mini size design saves installation space
- Anti-vibration design and light weight satisfy more installation conditions

Compression and Recording

- Scene-adaptive bitrate control technology would precisely allocate videos in eSSD according to the actual scene
- Full channel recording at up to 2 MP Lite resolution

Smart Function

- Deep learning-based motion detection 2.0
- Smart search for efficient playback



Specification

Motion Detection 2.0		
Human/Vehicle Analysis	Deep learning-based motion detection 2.0 is enabled by default for all analog channels,	
	it can classify human and vehicle, and extremely reduce false alarms caused by objects	
	like leaves and lights;	
	Quick search by object or event type is supported;	
Recording		
Video Compression	H.265 Pro/H.265	
Encoding Resolution	1080p Lite/720p/720p Lite/WD1/4CIF/CIF/QVGA	
Frame Rate	Main stream:	
	1080p Lite/720p/720p Lite/WD1/4CIF@25 fps (P)/30 fps (N)	
	Note:	
	1080p Lite/720p is 15 fps by default	
	Sub-stream:	
	4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps (N)	
Video Bitrate	According to the actual scene, scene-adaptive bitrate control technology would	
	automatically allocates appropriate bitrate to ensure the stability of recording period.	
Stream Type	Video, Video & Audio	
	Note: In order to protect privacy, the device will only record video (without audio) by	
	default. If you want to record audio, you shall manually enable audio recording. For	
	operation details, refer to the user manual.	
Audio Compression	G.711u	
Audio Bitrate	64 Kbps	
Video and Audio		
IP Video Input	1-ch	
	Up to 1080p resolution	
	Support H.265+/H.265 IP cameras	
Analog Video Input	4-ch	
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection	
HDTVI Input	1080p25, 1080p30, 720p25, 720p30	
AHD Input	1080p25, 1080p30, 720p25, 720p30	
CVBS Input	Support	
HDCVI Input	1080p25, 1080p30, 720p25, 720p30	
HDMI Output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz	
VGA Output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz	
Video Output Mode	HDMI/VGA simultaneous output	




Audio Input	4-ch via coaxial cable	
Audio Output	1-ch via HDMI	
Synchronous playback	4-ch	
Network		
Total Bandwidth	64 Mbps	
	Incoming bandwidth: 4 Mbps	
Network Protocol	TCP/IP, DHCP, HiLookVision, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP™, HTTPS	
Remote Connection	32	
Network Interface	1, RJ45 10/100 Mbps self-adaptive Ethernet interface	
Auxiliary Interface		
Capacity	Built-in 330 GB eSSD (300 GB available)	
	Note:	
	The device can store about 2 weeks videos for 4-ch analog cameras (default parameters),	
	this estimation is for reference only.	
USB Interface	Rear panel: 2 × USB 2.0	
Alarm In/Out	N/A	
General		
Power Supply	12 VDC, 1 A	
Consumption	\leq 5.4 W (with eSSD)	
Working Temperature	-10 °C to 45 °C (14 °F to +113 °F)	
Working Humidity	10% to 90%	
Dimension (W × D × H)	151 × 121 × 46 mm (5.94 × 4.76 × 1.81 inch)	
Weight	≤ 0.5 kg (with eSSD, 1.1 lb.)	

Note:

Analog and IP signal input types are not configurable, and analog channel cannot be disabled to increase the maximum accessible number of network cameras.

HiLcok

Physical Interface



Available Model

DVR-E04G-B



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



You Tube





©Hikvision Digital Technology Co., Ltd. 2022 I Data subject to change without notice I