Hilook

DVR-E08G-D 8-ch 1080p Lite 1U H.265 eSSD DVR

Key Feature

- Powered by eSSD technology
- Deep learning based human and vehicle targets classification of Motion Detection 2.0
- Scene-adaptive bitrate control video compression
- Up to 1080p Lite@15 fps encoding capability
- Low power consumption
- Audio via coaxial cable



Built-In SSD

- Minimalist eSSD design brings low power consumption
- Integrated storage design provides the plug-and-play device use

Easy Installation

- Mini size design saves installation space
- Anti-vibration design and light weight satisfy more installation conditions

Compression and Recording

- Scene-adaptive bitrate control technology would precisely allocate videos in eSSD according to the actual scene
- Full channel recording at up to 2 MP Lite resolution

Smart Function

- Deep learning-based motion detection 2.0
- Smart search for efficient playback



Specification

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motion detection 2.0 is enabled by default for all analog channels,
	it can classify human and vehicle, and extremely reduce false alarms caused by objects
	like leaves and lights;
	Quick search by object or event type is supported;
Recording	
Video Compression	H.265 Pro/H.265
Encoding Resolution	1080p Lite/720p/720p Lite/WD1/4CIF/CIF/QVGA
Frame Rate	Main stream:
	1080p Lite/720p/720p Lite/WD1/4CIF@15 fps
	Note:
	1080p Lite/720p is 15 fps by default
	Sub-stream:
	CIF/QVGA@15 fps
Video Bitrate	According to the actual scene, scene-adaptive bitrate control technology would
	automatically allocates appropriate bitrate to ensure the stability of recording period.
	Video, Video & Audio
Stream Type	Note: In order to protect privacy, the device will only record video (without audio) by
	default. If you want to record audio, you shall manually enable audio recording. For
	operation details, refer to the user manual.
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	2-ch
	Up to 5 MP resolution
	Support H.265+/H.265 IP cameras
Analog Video Input	8-ch
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTVI Input	1080p25, 1080p30, 720p25, 720p30
AHD Input	1080p25, 1080p30, 720p25, 720p30
HDCVI Input	1080p25, 1080p30, 720p25, 720p30
CVBS Input	Support
HDMI Output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz
VGA Output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz




Video Output Mode	HDMI/VGA simultaneous output
Audio Input	8-ch via coaxial cable
Audio Output	1-ch via HDMI
Synchronous playback	8-ch
Network	
Total Bandwidth	72 Mbps
	Incoming bandwidth: 8 Mbps
Remote Connection	32
Network Protocol	TCP/IP, DHCP, HiLookVision, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP™, HTTPS
Network Interface	1, RJ45 10/100 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
Capacity	Built-in 1024 GB eSSD (960 GB available)
	Note:
	The device can store about 4 weeks videos for 8-ch analog cameras (default parameters),
	this estimation is for reference only.
USB Interface	Rear panel: 2 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC, 1 A
Consumption	\leq 6.2 W (with eSSD)
Working Temperature	-10 °C to 45 °C (14 °F to 113 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	151 × 121 × 46 mm (5.94 × 4.76 × 1.81 inch)
Weight	≤ 0.5 kg (with eSSD, 1.1 lb.)

Note:

Analog and IP signal input types are not configurable, and analog channel cannot be disabled to increase the maximum accessible number of network cameras.

HiLcok

Physical Interface



6

Available Model

VGA interface

DVR-E08G-D

3



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

in Hikvision



HikvisionHQ



You Hik Cor

GND

Hikvision Corporate Channel



©Hikvision Digital Technology Co., Ltd. 2022 I Data subject to change without notice I