

DS-PC2002-WECKV **Controle Wireless**



- Operação: arme e desarme
- Função de bloqueio e desbloqueio do controle
- Totalmente configurável através do aplicativo
- Salto de frequência contra interferência para uma transmissão confiável

▪ Especificações

Características elétricas	
Humidade de operação	10% a 90%
Temperatura de operação	-10 °C a +55 °C (-4 °F a +122 °F)
Vida útil da bateria	Até 2 anos (tempo em standby)
Transmissão wireless	
Frequência RF	868 MHz
Módulação RF	2GFSK
Distância do sinal RF	500 m (área aberta)
Geral	
Mateiral da carcaça	Plástico
Cor	Branco
Peso	15 g
Dimensões (LxAxP)	35.0 mm × 64.1 mm × 10.9 mm

▪ Modelo disponível

DS-PC2002-WBCKV

▪ Acessórios opcionais

DS-K1T672MX Terminal de reconhecimento facial	DS-K1T672MX-QR Terminal de reconhecimento facial	DS-K1T672MFWX Terminal de reconhecimento facial	DS-K1T672MWX-QR Terminal de reconhecimento facial	DS-KAB670-WE Módulo periférico
				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq