

## DS-A72 Series Enterprise Network Storage

### Introduction

The DS-A72 series is the high-performance and high-reliability enterprise-class storage solution, offering 4 to 8 Gbps bandwidth and large-scale storage space. With dual 64-bit multi-core processors, reliable structure and RAID 6 technology, the product meets requirements of high performance and strictly ensures data security.



### Features and Functions

#### High-performance and Scalable Hardware Platform

- Modular design.
- Dual 64-bit multi-core processor.
- 8 to 128 GB high-speed cache.
- SAS2.0 and PCI-E2.0.
- 4U chassis, 24/36 HDDs; 8U chassis, 48/72 HDDs.
- Four to eight 1000M network interface, supporting SAS cascading, scalable 10G network interface.

#### HDD Detection and Repair/RAID Optimization

- Detection before operation.
- Detection in operation.
- Fault repair.
- RAID 0, 1, 3, 5, 6, 10, 50, VRAID.
- Global and local hot spare.
- Quick RAID building.
- Capability of cascading up to two storage enclosures behind a single SAS port.

#### Advanced Data Protection

- Synchronous backup of key information in system disk and HDD.
- RAID-based tamper-proof data technology.
- Auto data synchronization between devices.
- Volume clone technology.

#### Energy Efficient

- CPU load balance.
- Auto fan tuning.
- HDD sleeping.

#### User-Friendly UI

- Quick configuration
- Varied alarm management.
- SADP protocol supported.
- SNMP supported.

#### Surveillance-Specialized Direct Storage (Direct Streaming Mode)


- Space pre-allocation strategy.
- Direct storage for mixed video.
- Support direct IP camera/DVR/NVR streaming and recording.
- Support camera access through RTSP, ONVIF and PSIA protocol.
- Support alarm/scheduled/manual recording.
- Automatic network replenishment (ANR), timely uploading, and video loss alarm.
- Internal/external backup of data.
- Lock key videos.
- Search, play, and download videos by video type or video time.



## Specifications

Model		DS-A72024R	DS-A72072R	
Performance	Direct Streaming Mode: video (2 Mbps) + picture	820-ch recording + playback		
Controller	Processor	Dual 64-bit multi-core processor		
	Cache	8 GB (extendable to 128 GB)		
Storage	HDD slot	24	72	
	Interface/capacity	SATA/1 TB, 2 TB, 3 TB, 4 TB, 6 TB, 8TB,10TB,12TB		
	Hot-swapping	Supported		
	RAID	RAID 0, 1, 3, 5, 6, 10, 50, VRAID, JBOD, hot spare		
Network	Protocol	iSCSI, RTSP, ONVIF, PSIA		
External interface	Data	4, 1000M Ethernet interface (4 × 1GbE or 2 × 10GbE is extendable)	4, 1000M Ethernet interface	
	Management	1, 100M Ethernet interface	1, 100M Ethernet interface	
	SAS	Supported		
	COM	1, for HyperTerminal or UPS		
	USB	4		
	VGA	1		
General	Power supply	Redundancy (1 + 1)	Redundancy (2 + 1)	
	Consumption (with HDDs)	<ul style="list-style-type: none"> <li>● Operating: ≤ 410 W (1398 BTU with 24 HDDs)</li> <li>● Rated: ≤ 875 W</li> </ul>	<ul style="list-style-type: none"> <li>● Operating: ≤ 850 W (2899 BTU with 72 HDDs)</li> <li>● Rated: ≤ 1360 W</li> </ul>	
	Temperature	<ul style="list-style-type: none"> <li>● Operating: 5 °C to 35 °C (41 °F to 95 °F)</li> <li>● Storing: -20 °C to +70 °C (-4 °F to +158 °F)</li> </ul>		
	Humidity	<ul style="list-style-type: none"> <li>● Operating: 20% to 80% RH (non-condensing/frozen)</li> <li>● Storing: 5% to 90% RH (non-condensing/frozen)</li> </ul>		
	Chassis	19-inch 4U	19-inch 8U	
	Dimensions (W × D × H)	445 × 746 × 175 mm (17.5 × 29.4 × 6.9 in)	445 × 860 × 345 mm (17.5 × 33.9 × 13.6 in)	
	Weight (without HDDs)	≤ 40 kg (88.2 lb)	≤ 52 kg (114.6 lb)	

## Typical Application



## Available Models

DS-A72024R, DS-A72072R

## Available HDDs

Hikvision Tested and recommended HDDs

Seagate **MAKARA Series** (eg. ST8000NM0055) / Seagate **MakaraBP Series** (eg. ST6000NM0115) / **WD RE series** (eg. WD8002FRYZ-31) /

**HGST 7k6000 series** (eg. HUH728080ALE600)

**Note:** Enterprise HDD strong recommended when used in RAID mode and ISCSI application due to more stability design features; if Surveillance HDD need to be Used, please consult with Hikvision Sales.

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (0) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

000308170207