

HIKVISION®





GREAT INNOVATION
FROM DEEP INSIDE
**A NEW GENERATION OF
DF SERIES PTZ CAMERAS**

A NEW GENERATION OF DF SERIES PTZ CAMERAS

DF Series PTZ Cameras are designed with excellent pan, tilt and zoom capabilities for round-the-clock operation – meeting and exceeding customer's critical needs across vertical markets. To take this great technology over the next horizon, Hikvision has launched a new generation of DF Series Cameras with tremendous innovation while maintaining nearly the same, perfectly-suited housings.

The new DF Series – designed around an entirely new platform – come with various innovative features. Revolutionary dual-sensor DarkfighterX, 50x super zoom with OIS, Rapid-Focus, the latest deep learning algorithm and H.265+ codec are all integrated into this series to better fulfill every challenging need in the industry.





FEATURES OF NEW DF SERIES

1 DarkFighterX



Conventional camera



DarkFighter camera




DarkFighterX camera

DarkFighterX

- Higher brightness
- Better color fidelity
- Sharper edge
- Less noise and blur

* Note: only for DS-2DF8225IH-AEL(W)



Revolutionary Dual-Sensor Design


One sensor captures black and white images while the other captures color images. The two images then merge into one with full color and sufficient brightness.

* Note: only for DS-2DF8225IH-AEL(W)

2 4K DarkFighter



4K conventional PTZ



4K DarkFighter PTZ

Outdoor low-light performance with 4K resolution

Sharper images with less noise to enhance indoor surveillance.

3 OPTICAL IMAGE STABILIZATION



Optical image stabilization off



Optical image stabilization on

Optical Image Stabilization

Equipped with gyroscopes, OIS lenses, and dedicated processors, Hikvision PTZ cameras can sense vibrations, then makes quick and precise compensations to stabilize the image.

* Note: only for DS-2DF8250I5X-AEL(W)

4 UPGRADED ZOOM



20x - 25x



30x - 32x



36x




50x

5 H.265+ CODEC

Most Efficient Use of Bandwidth

How many 2MP cameras can be carried by a 20Mb broadband network?



20 MB Broadband Network



Most Efficient use of Storage

How much storage capacity is needed for 8 pcs 2MP camera recording for a month?



Eight 2 MP cameras




5 TB of Data

6 EMBEDDED DEEP LEARNING ALGORITHM

Enhanced Smart Functions and Auto-Tracking

Deep Learning filters out false alarms caused by non-target objects such as animals, leaves or light changes, and greatly improves the accuracy of Smart functions and auto-tracking.



APPLICATION SCENARIOS



Squares



Harbor



City



Venue Stadium



Intersections



Airports



School



Parking



Warehouse

PRODUCT SHOWCASE



DS-2DF8225IH-AEL(W)
DarkfighterX 2MP
25× IR Network Speed
Dome

- 2x 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Ultra-low light:
- Color: 0.001 Lux @ (F1.5, AGC ON)
- B/W: 0.0001 Lux @ (F1.5, AGC ON)
- 25× Optical Zoom, 16× Digital Zoom
- Digital WDR, 3D DNR, HLC, BLC
- Up to 200 m IR distance
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF8225IX-AEL(W)
2MP 25× Network IR
Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination
- Color: 0.002 Lux @ (F1.5, AGC ON)
- B/W: 0.0002 Lux @ (F1.5, AGC ON)
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression
- Support rapid focus



DS-2DF8236I5X-AEL(W)
2MP 36× Network Laser
Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination:
- Color: 0.002 Lux @ (F1.5, AGC ON)
- B/W: 0.0002 Lux @ (F1.5, AGC ON)
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 500 m laser distance
- Support H.265+/H.265 video compression
- Support rapid focus

PRODUCT SHOWCASE



DS-2DF8236IX-AEL(W)
2MP 36x Network IR Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.002 Lux @([F1.5, AGC ON])
- B/W: 0.0002 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression
- Support rapid focus



DS-2DF8250I8X-AEL(W)
2MP 50x Network Laser Speed Dome

- 1/2.8" Progressive Scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.05 Lux @([F1.8, AGC ON])
- B/W: 0.01 Lux @([F1.8, AGC ON])
- 50× Optical Zoom, 16× Digital Zoom
- 120dB WDR, 3D DNR, HLC, BLC
- Optical Image Stabilization
- Up to 800 m laser distance
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF8250I5X-AEL(W)
2MP 50x Network IR Speed Dome

- 1/2.8" Progressive Scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.05 Lux @([F1.8, AGC ON])
- B/W: 0.01 Lux @([F1.8, AGC ON])
- 0 Lux with IR
- 50× Optical Zoom, 16× Digital Zoom
- 120dB WDR, 3D DNR, HLC, BLC
- Optical Image Stabilization
- Up to 500 m IR distance
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF8425IX-AEL(W)
4MP 25x Network IR Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 2560 × 1440 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 0 Lux with IR
- 25× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression
- Support rapid focus



DS-2DF8436I5X-AEL(W)
4MP 36x Network Laser Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 2560 × 1440 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 500 m laser distance
- Support H.265+/H.265 video compression
- Support rapid focus



DS-2DF8436IX-AEL(W)
4MP 36x Network IR Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 2560 × 1440 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression
- Support rapid focus



DS-2DF8825IX-AEL(W)
8MP 25x Network IR Speed Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 25× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression



DS-2DF8836I5X-AEL(W)
8MP 36x Network Laser Speed Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 500 m laser distance
- Support H.265+/H.265 video compression



DS-2DF8836IX-AEL(W)
8MP 36x Network IR Speed Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR distance
- Support H.265+/H.265 video compression



DS-2DF7225IX-AEL(W)
2MP 25x Network IR Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 150 m IR distance
- Support H.265+/H.265 video compression



DS-2DF7232IX-AEL(W)
2MP 32x Network IR Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 32× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Smart IR
- 24VAC & Hi-PoE
- Up to 150 m IR distance
- Support H.265+/H.265 video compression



DS-2DF6225X-AEL
2MP 25x Network Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.002 Lux @([F1.5, AGC ON])
- B/W: 0.0002 Lux @([F1.5, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Optical Defog
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression

PRODUCT SHOWCASE



DS-2DF5225X-AEL
2MP 25× Network Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF5232X-AEL
2MP 32× Network Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 32× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF5225X-AE3
2MP 25× Network Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF5232X-AE3
2MP 32× Network Speed Dome

- 1/2.8" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. Illumination:
- Color: 0.05 Lux @([F1.6, AGC ON])
- B/W: 0.01 Lux @([F1.6, AGC ON])
- 32× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC
- 24 VAC & Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A225-AEL
2MP 25× Network Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.002 Lux @([F1.5, AGC ON])
- B/W: 0.0002 Lux @([F1.5, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A236X-AEL
2MP 36× Network Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Min. illumination:
- Color: 0.002 Lux @([F1.5, AGC ON])
- B/W: 0.0002 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A425X-AEL
4MP 25× Network Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 2560 × 1440 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 25× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A436X-AEL
4MP 36× Network Speed Dome

- 1/1.9" progressive scan CMOS
- Up to 2560 × 1440 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A825X-AEL
8MP 25× Network Speed Dome


- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 25× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression



DS-2DF6A836X-AEL
8MP 36× Network Speed Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
- Color: 0.005 Lux @([F1.5, AGC ON])
- B/W: 0.0005 Lux @([F1.5, AGC ON])
- 36× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC, Defog, EIS
- 24 VAC &Hi-PoE
- Support H.265+/H.265 video compression

PRODUCT COOPERATION PROPOSAL



With the official launch of Hikvision's Integration Partner Program, we are glad to offer an opportunity for extensive cooperation between Hikvision and its various partners. This effort will harness the power of combined networks to create a joint value proposition and gain the leading edge in the market.

When joining this program as a Hikvision Strategic Partner, you will enjoy access to a wealth of technical and commercial resources, and we will ensure that your solution enjoys strategic marketing through our communication channels. You will also get instant access to our entire sales organisation. A vital part of our program is streamlined online communication with our technical teams as well as the tools to plan the go-to-market activities.

Marketing

- Partner application recommendation on Hikvision global network
- Co-exhibition opportunities
- Co-branded success stories
- Global press releases
- Social media exposure
- Branding opportunities
- Hikvision product materials

Technical Support

- Qualified integration service
- Dedicated integration development support
- Integration priority service
- Targeted product & cooperation value proposal
- In-depth training

Business Development

- Regular local networking opportunities
- Dedicated partner management
- Project-sharing possibilities

Hikvision DarkFighterX Cameras have been officially released all around the world, and are project-ready from all of our distribution networks and branch offices, ensuring a quarantined logistic supply and local technical support.

In order to build a better joint value proposition with our DarkfighterX cameras, we will take the following integration approaches based on the partner's strengths:





GREAT INNOVATION
FROM DEEP INSIDE
A NEW GENERATION OF
DF SERIES PTZ CAMERAS

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 03511172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-1031-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

Follow us on social media to get the latest product and solution information



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq

www.hikvision.com