# **HIKVISIO**N°

# HIKCENTRAL PROFESSIONAL SERVER

- HikCentral Professional installed by default
- VSS licences activated





# Product Specification

Performance	Key Feature	HikCentral-VSS-Base-HW-64Ch	HikCentral-VSS-Base-HW-300Ch
HikCentral Professional	Cameras	64 (Expandable to 3,000)	300 (Expandable to 3,000)
	Events or Alarms Storage	100/s without pictures 20/s (with pictures stored in SYS Server) 80/s (with pictures stored in Recording Server)	
	Events or Alarms sent to clients	120 events or alarms/s 100 Clients/s (Control Client & Mobile Client)	
Hardware	Processor	Intel® Xeon® E-2124	
	Operating System	Microsoft Windows Server® 2016 multilingual operating system	
	Memory	16G DDR4 DIMM slots, Supports UDIMM, up to 2666 MT/s, 646B Max. Supports registered ECC	
	Storage Controllers	Internal Controllers: SAS_H330 Software RAID: PERC S140	
		External HBAs: 12Gbps SAS HBA (non-RAID)	
		Boot Optimized Storage Subsystem: 2x M.2 240GB (RAID 1 or No RAID), 1x M.2 240GB (No RAID Only)	
	Drive Bays	1T 7.2K SATA×2	

# 🖸 Benefits



# **Integrated In One Unit**

High-end hardware, operating system and HikCentral Professional software integrated in one unit



# **3 Years Aftersales Service**

Technical support for Hik-Central software is provided by Hikvision Hardware & Operation System are covered by Dell "ProSupport Plus" Enterprise services, with 24X7 remote technical support and 4 Hours Onsite Response



# **Cost Effective**

A competitive price to get both high-end hardware and software (pre-installed with 64/300-ch VSS license base)



### Ease of Use

Plug and play, no additional activation required, embedded wizard makes each functional module easy for users to learn and configure

# Product Features



## **Easy Operation**

Embedded wizard for video, access control, entrance & exit, alarm detection and signage applications, easy for users to learn and configure.



### **Easy Maintenance**

Visual display system status in real-time, to quickly notice and locate abnormal situations. All system history records are trackable.



# Self-defined Control Panel

Each operator can self-define their own control panel and web panel, that each individual is able to focus on his own part and prevent system configuration errors caused by incorrect operation.



# **Application Linkage**

Operators can build linkage between different applications. E.g. access control detects intrusion and triggers CCTV to do recording.



# **Visualised Statistic Reports**

Intelligent data from multiple applications are centralised at HikCentral Professional. System translates them into visualised statistic reports, to help users making decisions more easily.



# **System Integration**

Server system can integrate with third party platform & hardware through OpenAPI and Optimus which is the system-level middleware product, committed to building up an information bridge between HikCentral and third party systems.

# **HIKVISION**°

Hikvision UK & Ireland 4 The Square, Stockley Park, Uxbridge, UB11 1ET presales.uk@hikvision.com



