










Hikvision Temperature Screening Product Kit list

1. High-end fixed camera solution

Product Model	Picture	Description	Mark
DS-2TD2636B-15/P DS-2TD2636B-13/P DS-2TD2637B-10/P		Thermal: 384 × 288; Lens: 10/13/15mm Optical: 4MP; Optical Lens: 4/6mm; Accuracy: ±0.5°C Working temperature: 10~35°C	Installation height: 1.7m~2.5m Detection distance: 10mm: 2~7m 13mm:2.5-7m 15mm: 2.5-9m
DS-2907ZJ		UNC 1/4\" -20 Tripod	Optional, camera also support wall/ceiling mount
DS-2909ZJ		Tripod adapter	
DS-3E0109P-E(C)		8 PoE ports switch	
DS-D5022FN		22\" monitor, VGA/HDMI input	
DS-7608NI-I2/8P		8 IP channels NVR. 8 PoE ports, alarm I/O: 4/1	Optional, customer can also use IVMS for alarm management
DS-2TE127-G4A		Improve camera accuracy to ±0.3°C Effective emissivity: 0.97±0.02 Operating temperature: 0~40°C	Optional
IVMS-4200		Hikvision entry level VMS for small quantity camera	Optional
Hik-Central		Hikvision professional level VMS for large quantity camera	Optional





2. Entry level fixed camera solution



Product Model	Picture	Description	Mark
DS-2TD2617B-3/PA DS-2TD2617B-6/PA DS-2TD1217B-3/PA DS-2TD1217B-6/PA		Thermal: 360*120; Lens: 3/6mm Optical: 4MP; Optical Lens: 4/8mm; Accuracy: $\pm 0.5^{\circ}\text{C}$ Working temperature: 10~35°C	Recommended installation height: 1.5m Detection distance: 3mm: 0.8-1.5m 6mm: 1.5-3m
DS-2907ZJ		UNC 1/4"-20 Tripod	
DS-2909ZJ/DS-2908ZJ		Tripod adapter DS-2909ZJ for bullet camera, DS-2908ZJ for turret camera	
DS-3E0109P-E(C)		8 PoE ports switch	
DS-D5022FN		22" monitor, VGA/HDMI input	
DS-7608NI-I2/8P		8 IP channels NVR. 8 PoE ports, alarm I/O: 4/1	Optional, customer can also use IVMS for alarm management
DS-2TE127-G4A		Improve camera accuracy to $\pm 0.3^{\circ}\text{C}$ Effective emissivity: 0.97 ± 0.02 Operating temperature: 0~40°C	Optional
IVMS-4200		Hikvision entry level VMS for small quantity camera	Optional
Hik-Central		Hikvision professional level VMS for large quantity camera	Optional

3. Deepinmind solution (Mask detection+ Attendance report)

Product Model	Picture	Description	Mark
Temperature screening camera		DS-2TD2617B-3/PA DS-2TD2636B-15/P DS-2TD2617B-6/PA DS-2TD2636B-13/P DS-2TD1217B-3/PA DS-2TD2637B-10/P DS-2TD1217B-6/PA	
DS-2907ZJ		UNC 1/4" -20 Tripod	
DS-2909ZJ/DS-2908ZJ		Tripod adapter DS-2909ZJ for bullet camera, DS-2908ZJ for turret camera	
DS-3E0109P-E(C)		8 PoE ports switch	
DS-D5022FN		22" monitor, VGA/HDMI input	
iDS-7716NXI-I4/16P/X(B)		Deepinmind NVR, 16-ch mask detection, 16-ch attendance check, 16 PoE ports	
DS-2TE127-G4A		Improve camera accuracy to $\pm 0.3^{\circ}\text{C}$ Effective emissivity: 0.97 ± 0.02 Operating temperature: $0 \sim 40^{\circ}\text{C}$	Optional
IVMS-4200		Hikvision entry level VMS for small quantity camera	Optional
Hik-Central		Hikvision professional level VMS for large quantity camera	Optional

4. Handheld solution

Product Model	Picture	Description	Mark
DS-2TP21B-6AVF/W		Thermal: 160 × 120, 6.2mm, 25° × 19° Optical: 2MP Bi-spectrum image fusion; WIFI, Audio alarm Accuracy: ±0.5°C Distance: 1.5-2.5m	
DS-2907ZJ		UNC 1/4" -20 Tripod	
IVMS-4200	 iVMS-4200.	Hikvision entry level VMS for small quantity camera	Optional
Hik-Thermal		Hikvision Thermal app for mobile devices	Optional

Product Model	Picture	Description	Mark
DS-2TP31B-3AUF		Thermal: 160 × 120, 3mm, 25° × 19° Accuracy: ±0.5°C Distance: 1m	
DS-2907ZJ		UNC 1/4" -20 Tripod	