

DS-2CE76D3T-ITMF 2 MP EXIR Turret Camera



- 2 MP turret camera
- Strong night performance, capturing images in ultra-low light down to 0.005 lux
- Clear imaging even against strong back lighting due to 120 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- EXIR 2.0: advanced infrared technology with 30 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)



Specification


- Specification			
Camera			
Image Sensor	2.0 megapixel progressive scan CMOS		
Max. Resolution	1920 (H) × 1080 (V)		
Min. Illumination	0.005 Lux@(F2.0, AGC ON), 0 Lux with IR		
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s		
Day & Night	IR Cut Filter		
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°		
Signal System	PAL/NTSC		
Lens			
Lens Type	2.8 mm, 3.6 mm, 6 mm		
Focal Length & FOV	106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)		
Lens Mount	M12		
Illuminator			
Supplement Light Type	IR		
Supplement Light Range	Up to 30 m		
Smart Supplement Light	Yes		
Image			
Image Parameters Switch	STD/HIGH-SAT		
Image Settings	Brightness, Mirror, Sharpness, AGC		
Frame Rate	PAL: 1080p@25fps		
	NTSC: 1080p@30fps		
Day/Night Mode	Auto/Color/BW (Black and White)		
Wide Dynamic Range (WDR)	≥120 dB		
Image Enhancement	WDR,BLC,HLC		
Noise Reduction	3D DNR		
Interface			
Video Output	Switchable TVI/AHD/CVI/CVBS,1 HD analog output		
General			
Power	12 VDC ±25%, max. 4.6 W		
	*You are recommended to use one power adapter to supply the power for one		
	camera.		
Material	Metal		
Dimension	89.47 mm × 68.2 mm (3.52" × 2.68")		
Weight	Approx. 240 g (0.53 lb.)		
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)		
Language	English		
Approval			
Protection	IP67		


Available Model

DS-2CE76D3T-ITMF



Dimension





Accessory

Optional

PC110T	PM	CM	CBXS Junction Box
Wall Mount	Vertical Pole Mount	Corner Mount	
	***		.



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







