HeatPro Bi-Spectrum Thermal & Optical Cameras Optimize Security for High End Villas, Apartments & Multi-Unit Residential Applications

Residential properties need to protect property perimeters, deter crime, and prevent theft, and protect against fire. HeatPro Bi-Spectrum Cameras provide outstanding perimeter protection and early fire detection with warnings using its thermal module to see through smoke, fog, dense foliage and challenging weather.



Current Challenges Protecting Residences

70 percent of residential burglaries occur at night

- High cost of 24/7 security
- · Conventional cameras perform poorly at night

No early fire detection and warnings

- Smoke detectors do not provide visual warnings
- · Early, advanced notices not available in case of fire

Complicated setup

- · Systems are often complex and expensive
- Lacking privacy protection

HeatPro



Exceptional 24/7 Performance

The Solution: HeatPro Bi-Spectrum Cameras

- Works in any environment
- Reduces false alarms
- Built-in flashlight and speaker provide instant warnings



Instant Temperature & Fire Detection

- Monitors temperature exceptions and triggers a pre-alarm notice
- Provides visual dashboard of temperature measurement



HIKAISION

Simple Configuration

- Easy VCA setup with tutorial
- Works with Hikvision I and K series NVRs
- Protects user's privacy



Real-Time Fire Detection HeatPro's large field-of-view covers wide areas where a fire could occur.



Visibility at Night

HeatPro secures backyards and perimeters at night with superior thermal visibility. The thermal module can see through dense foliage, fog and smoke.



Parking Lots & Garages

Temperature except alarm can monitor charging stations, electricity boxes and any potential fire risk.



Perimeter Protection

HeatPro offers highly accurate coverage over large areas and detects intrusion and line crossing activity.



Swimming Pools Perimeter protection with temperature exception for added safety.

<complex-block>

FLEXIBLE SOLUTIONS

Economical Solution

HeatPro cameras are easily accessible from the Hik-Connect app or using Hikvision I or K series NVRs.



HeatPro Camera Local Monitor Hik-Connect



PRODUCT SHOWCASE

- Resolution: 160 x 120 for thermal, 4 MP for visible light
- VCAs: Line crossing, intrusion detection
- Temperature accuracy: ±14.4° F (±8° C)
- Temperature measurement range: -4° to 302° F (-20° to 150° C)
- Built-in strobe light and audio alarm

Bi-spectrum



Bullet

DS-2TD1217-2/3/6/PA

DS-2TD2617-3/6/10/PA

FOCUSED ON YOUR SUCCESS



©2021 Hikvision USA Inc. and Hikvision Canada Inc. All rights reserved. Hikvision is a registered trademark of Hikvision Digital Technology Co., Ltd. in the US, Canada and other countries. Product specifications and availability are subject to change without notice.