

## VT-3E0524-E(B) 24 Port Gigabit Unmanaged Switch



- 24 x 1000 M Ethernet ports
- Supports IEEE 802.3, IEEE 802.3u and IEEE 802.3x
- 1000 M network access
- Wire-speed forwarding and non-blocking design
- Store-and-forward switching
- Solid high-strength metal shell
- Fan-free design with high reliability

## ▪ Specification

Model		VT-3E0524-E(B)
<b>Network Parameters</b>	Ports	24 × Gigabit RJ45 port
	MAC Address Table	8 K
	Switching Capacity	48 Gbps
	Packet Forwarding Rate	35.72 Mpps
	Internal Cache	4.10 Mbits
<b>General</b>	Shell	Metal material, fan-free design
	Net Weight	1.60 kg (3.50 lb)
	Gross Weight	2.47 kg (5.44 lb)
	Dimensions (W × H × D)	335.0 mm × 44.5 mm × 175.8 mm (13.2" × 1.8" × 6.9")
	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Storage Temperature	−40 °C to 85 °C (−40 °F to 185 °F)
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	220 VAC, 50/60 Hz, Max. 0.7 A
	Installation Mode	Metal material, fan-free design
<b>Approval</b>	EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7:2020), RCM (AS/NZS CISPR 32: 2015)
	Safety	UL (UL 60950-1), CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	CE-RoHS (2011/65/EU), WEEE (2012/19/EU), Reach (Regulation (EC) No.1907/2006)

## ▪ Available Model

VT-3E0524-E(B)

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

