

DS-PK00(M)-LCD Series

LCD Keypad

The DS-PK00-LCD series is used for connecting to security control panel. It can work with keyfobs for arming/disarming. By using indicators and sounds for alarm. It can support security control panel configuration.



DS-PK00M-LCD



DS-PK00-LCD

AVAILABLE MODEL

DS-PK00-LCD

DS-PK00M-LCD (supports arm/disarm via Mifare card)

Note: DS-PK00(M)-LCD series keypad apply to all wired control panel

MAIN FEATURES

- Arming and disarming by swiping cards, and up to 32 cards can be added to the security control panel(DS-PK00M-LCD)
- Remote arming and disarming via keyfob. Up to 32 wireless keyfobs can be added
- One-push to arm, and by using password to disarm
- Supports single zone arming and disarming
- Supports displaying the signal strength of GPRS
- Supports online programming
- Displaying real-time status of zones
- Upgrading security control panel via the client software
- IML manufacturing technology

SPECIFICATIONS

Model	DS-PK00-LCD	DS-PK00M-LCD
Button	12 , (0 1 2 3 4 5 6 7 8 9 * #)	
Indicator	5 , (Status, Running, Power, Arming, Perimeter Arming)	
Function Key	7 Function Keys (Project, Panic, Stay Arming, Away Arming, Bypass, Query, Exit)	
Tamper-Proof	Supported	
Uplink Communication	RS-485	
Panic Prompt	Buzzer	
Transmission frequency	433MHZ/868MHz	
Function	Programming, Arming/Disarming, Clearing Alarm, Bypass/Bypass Recovery, Project Test, Partition Operation, Relay Operation, Status Query	
Arming/Disarming via RF Remote Control	YES	
Arming/Disarming via Mifare Card	NO	YES
Power Consumption	1.5 W	
Working Temperature	-40°C ~ +70°C (-40°F ~ 158°F)	
Working Humidity	10% ~90%	